

SPECIFICATIONS



Model	Dimensions	Weight
CA4200	(42" Diameter x 30.5"H)	89 lbs
CA4800	(48" Diameter x 30.5"H)	112 lbs
CA4242	(42"L x 42"W x 30.5"H)	92.5 lbs

*Intended for indoor use only



DETAILS

Finishes

See Design Guide for finish options.

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

Factory Ballasting (150 lbs)

*Ballastable up to 200 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

Assembly

Refer to manufacturer's instructions for assembly.

Fabrication & Material

Base: One-piece, rotationally-molded polyethylene with lightly textured, maintenance-free surface which allows for easy cleaning. Specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability.

Laminate Top: Premium M3 Grade, 45 lb. density particle board table top core is sandwiched between 1/8" thick hardboard and faced with special 0.05" thick high pressure laminate for superior quality and long term durability. Molded edge is radiused for safety and comfort, pressure fused to the top, rendering it firmly attached and highly sanitary. Embedded T-nuts secure top to base with tight steel-to-steel connection for maximum long term reliability. Robust 1.5" thick edge profile. Made in the U.S.A.

Installation

Ballast weighting required to validate warranty. Recommend 200 pounds of dry sand or gravel ballast. On site materials not supplied by Norix.

Warranty

10 year limited replacement warranty.

Maintenance

Top: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product.

Base: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

TESTING

Performance Test Standards

Product tested to 1,000 lb static load

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospital's guidelines