



Model	PX40
Weight	23 lbs / 10.4 kg

Dimensions	in	cm
Height	18.1"	46
Depth	30.4"	77.2
Width	24"	61

Finishes

See Design Guide for finish options.

Options

- Bolt-Down Kit
- Ganging Kit
- Factory Ballasting (50 lbs / 22.7 kg)

**Ballastable up to 100 pounds (45.4 kg) of dry sand or gravel. On site ballast materials not supplied by Norix.*

Assembly

None required.

Fabrication & Material

One-piece, rotationally-molded polyethylene with lightly textured maintenance-free surface which allows for easy cleaning. Ligature resistant design with no internal openings. A built-in drainage channel prevents pooling by allowing liquids to flow to the back of the seat and drain off the sides. Molded-in floor glides protect the floor from scratching without risking the safety of residents and staff. Molded-in access port with a threaded screw cap for ballast weighting capability. High-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution, and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability. Made in the U.S.A.

Warranty

5 year limited replacement warranty.

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

Performance Test Standards

- Tested to 750 lbs (340.2 kg) static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18") (113.4 kg from 45.7 cm)

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items

