

SPECIFICATIONS



Model

V311-2F

Weight

253 lbs

Dimensions

Seat Height 19.9"

Width 89.5"

Overall Height 56.5"

*Intended for indoor use only



DETAILS

Finishes

See Design Guide for finish options.

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Assembly

Assembly required. Refer to manufacturer's instructions

Installation

Attach wall-mount unit to wall using furnished mounting brackets. Anchors or bolts not included. Anchor legs to floor using provided concealed concrete expansion anchors.

Warranty

10 year limited replacement warranty

Fabrication & Material

Bolt together with tamper-resistant mechanical fasteners (supplied). Wall-mount.

Sides & Writing Surface: Heavy-duty, graffiti resistant, high-pressure laminate bonded to 45 lb. density particle board. T-mold vinyl edges are glued around circumference for tamper-resistance and security. Panels connect with internal barrel bolts.

Legs and Seat Support: 10" radius curved portions of the legs support the top and for additional strength are fully welded to the vertical tubes that support the seats. The tops of the curved tubes and the tops of the seat support tubes are fully welded to 6"x 6" x 1/4" thick steel plates. The bottoms of the seat tubes are fully enclosed to conceal floor-mounting anchors.

Legs: 3" diameter 14 gauge steel finished with black powder coat paint.

Seats: Option 1: Super Slammer Stone – 13" diameter high-density color impregnated compression molded composite that is highly scratch and stain resistant. Option 2: Stainless Steel – 14 gauge, type 304. One-piece 12" diameter with 1 1/2" drop edge. #4 finish. Made in the U.S.A.

Maintenance

Laminate Cabinet: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product.

Legs: Norix recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of powder coated steel.

Seat: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. For the deep-scrub cleaning of tougher stains, marks and debris, we recommend the use of Clorox® Clean-Up® Cleaner + Bleach or an equivalent cleaning solution. When cleaning stainless steel, Norix recommends the use of a cleaner made especially for stainless steel products.

TESTING

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.