Prodigy®
Storage Bed



Model	PRD130
Weight	120 lbs / 54.4 kg

Bed Dimensions	in	cm
Overall Length	78″	198.1
Overall Width	32″	81.3
Height	21″	53.3
Bed Deck Length	76″	193
Bed Deck Width	30″	76.2
Cubby Dimensions	**in**	**cm**
Cubby Height *(front)*	15.3″	38.9
Cubby Height *(back)*	14.2″	36.1
Cubby Width	29.3″	74.4
Cubby Depth	21″	53.3
Cubby Volume	**cu ft**	**m^3**
Cubby Volume	4.48	0.12

Note: Dimensional tolerances are +1% due to manufacturing process.

Mattress Size
30″x75″ (76.2x190.5 cm)

Finishes
See Design Guide for finish options.

Storage Compartment
Compatible with PB150 and PB200 Tank Box Property Storage.

**Intended for indoor use only*

GREENGUARD GOLD · TruGrain PROPRIETARY WOOD GRAIN TECHNOLOGY · RECYCLABLE PRODUCT · RECYCLABLE PRODUCT · MADE IN THE USA

Fabrication & Material
One-piece, 100% seamless, specially formulated polymer construction is structurally reinforced for superior durability, impact resistance and security. Rounded edges for added safety, grooved sleep surface for fluid management. Each piece is uniquely fashioned with proprietary TruGrain™ polymer formulation to replicate natural wood, and deliver a residential, non-institutional appearance. The seamless, one-piece construction delivers long-term, maintenance-free performance superior to wood in infection-control, fluid, tamper, infestation, contraband resistance and ligature resistant design. Contains a minimum of 30% recycled content. Made in the U.S.A.

Warranty
Lifetime warranty.

Maintenance
For routine and regular cleaning, Norix® recommends the use of Simple Green® or an equivalent cleaning product with a soft damp cloth. Prodigy® products are suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions. Bolt-down fasteners should be tight with no gaps larger than 1⁄16″ (0.2 cm) between the bottom of the bed and the floor. There should be no visible cracks in the caulk, if applied.

Installation
Proprietary ligature resistant floor anchoring system with concealed hardware (mechanism and all anchoring hardware included). Anchoring mechanism and hardware intended for concrete floors and/or walls. (Please consult contractor or facility management as necessary.) Security caulk may be applied to the perimeter after anchoring.

Patents
This product may be covered by US Patent Nos. US 11,712,113 B2 and additional patents pending.

Performance Test Standards
- Tested to 1,500 lbs (680.4 kg) static load.

Environmental Test Standards
- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards
- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 116, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- ASTM E1537 Test Method for Fire testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture

One Innovation Drive, West Chicago, IL 60185 | Phone: 630-231-1331 | Toll Free: 800-234-4900 | E-mail: furniture@norix.com
Specifications subject to change without notice. | ©2026 Norix Group, Inc. | All Rights Reserved. | Printed in U.S.A. 9/26