



Fabrication & Material

One-piece, rotationally-molded, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). The commercial-grade polyethylene material is also FDA-approved. Premium TruColor™ polymer is fully compounded for superior color consistency and durability. Made in USA.

Warranty

Lifetime Warrenty

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

Performance Test Standards

- Product tested to 500 lbs / 226.8 kg static load.

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- 16CFR 1500-14 Flammability
- 16CFR 1303 Lead Content in Surface Coating
- CPSIN Sec 01 Lead Content in Substrate
- CPSIA Sec 08 Phlate Content
- Meets or exceeds the requirements of ANSI/BIFMA X5.4-2012
- Meets or exceeds ASTM F963

Model	AM10
Weight	22 lbs / 10 kg

Dimensions	in	cm
Seat Height	14.3"	36.3
Width	17.5"	39.9
Length	43"	109.2
Overall Hight	22"	55.9

Finishes

See Design Guide for finish options.

Options

- On site Ballasting (50 lbs / 22.7 kg)

**Ballastable up to 50 lbs (22.7 kg) of dry sand. On site ballast materials not supplied by Norix.*

Assembly

None required.

Patents

Patents pending.

**Intended for indoor use only*

