

Arcadian Nightstand



Fabrication & Material

Rotationally molded high impact polyethylene is specially formulated for superior durability and impact resistance. The seamless, one-piece construction has no internal openings for added safety and security. A slightly textured surface delivers long-term, maintenance-free performance. Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Made in the U.S.A.

Warranty

Lifetime warranty.

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. Arcadian products are bleach/ water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

Installation

Bolt-down kit required for floor anchoring. Proprietary anchoring system with concealed hardware intended for concrete floors and/or walls. (Please consult contractor or facility management as necessary.) Security caulk may be applied to the perimeter after anchoring.

Performance Test Standards

- Product tested to 750 lbs (340.2 kg) static load.

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 116, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- ASTM E1537 Test Method for Fire testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture

Model	ARC250
Weight	28 lbs / 12.7 kg

Dimensions	in	cm
Height	23"	58.4
Overall Length	20"	50.8
Overall Width	20"	50.8
Cubby Volume	cu ft	m ³
Top Cubby	0.82	0.02
Bottom Cubby	1.4	0.04

**Note: Dimensional tolerances are +1% due to manufacturing process.*

Finishes

See Design Guide for finish options.

Options

- Factory Ballasting (35 lbs / 15.9 kg)

**Ballastable up to 35 pounds (15.9 kg) of dry sand. Factory ballasting option must be communicated at time of order; products are not field ballastable.*

Assembly

None required.

**Intended for indoor use only*

