


SPECIFICATIONS



Model

ARC250

Weight

28 lbs

*Intended for indoor use only

Dimensions

Width	20"
Depth	20"
Height	23"
Small Cubby Volume:	0.82 cu ft
Large Cubby Volume:	1.4 cu ft

Note: Dimensional tolerances are +1% due to manufacturing process.



DETAILS

Finishes

See Design Guide for finish options.

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

Factory Ballasting

*Ballastable up to 35 pounds of dry sand or gravel. Factory ballasting option must be communicated at time of order; products are not field ballastable.

Assembly

None required

Fabrication & Material

Rotationally molded high impact polyethylene is specially formulated for superior durability and impact resistance. The seamless, one-piece construction has no internal openings for added safety and security. A slightly textured surface delivers long-term, maintenance-free performance. Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Made in the U.S.A.

Installation

Bolt-down kit required for floor anchoring. Proprietary anchoring system with concealed hardware intended for concrete floors and/or walls. (Please consult contractor or facility management as necessary.) Security caulk may be applied to the perimeter after anchoring. Optional Norix® Authorized Installation services reinforce Limited Warranty.

Warranty

10 year limited replacement warranty.

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. Arcadian products are bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

TESTING

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Performance Test Standards

Product tested to 750 lbs static load.

Flammability Test Standards

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 116, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture