

SPECIFICATIONS



Model

ARC600

Weight

75 lbs

*Intended for indoor use only

Dimensions

Width 36"

Depth 24"

Height 30"

Note: Dimensional tolerances are +1% due to manufacturing process.



DETAILS

Finishes

See Design Guide for finish options.

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

Factory Ballasting

*Ballastable up to 50 pounds of dry sand or gravel. Factory ballasting option must be communicated at time of order; products are not field ballastable.

Assembly

None required

Fabrication & Material

Rotationally molded high-impact polyethylene is specially formulated for superior durability and impact resistance. The seamless, one-piece construction has no internal openings for added safety and security. A slightly textured surface delivers long-term, maintenance-free performance. Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Made in the U.S.A.

Installation

Bolt-down kit required for floor anchoring. Proprietary anchoring system with concealed hardware intended for concrete floors and/or walls. (Please consult contractor or facility management as necessary.) Security caulk may be applied to the perimeter after anchoring. Optional Norix® Authorized Installation services reinforce Limited Warranty.

Warranty

10 year limited replacement warranty.

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. Arcadian products are bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

TESTING

Performance Test Standards

Product tested to 1,000 static load

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 116, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture