## Affinity Armless Chair



### SPECIFICATIONS



| Model                         | Dimensions     |               | COM Yards   |     |
|-------------------------------|----------------|---------------|-------------|-----|
| A2                            | Seat Height    | 17.4″         | Total Yards | 1.5 |
| Weight                        | Seat Width     | 18.5″         | Seat Yards  | 1   |
| 20 lbs                        | Overall Height | 32.1" - 32.5" | Back Yards  | 0.5 |
|                               | Overall Depth  | 22.8″         |             |     |
| *Intended for indoor use only | Overall Width  | 20.3″         |             |     |



## DETAILS

#### Finishes

See Design Guide for finish options.

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

#### Options

Available in California TB133 compliant upholstery for fully upholstered chair only. Ganging bracket available.

#### Assembly

No assembly required

#### **Fabrication & Material**

Frame: Welded steel frames with durable metal seat pan for added strength and structural durability.

Cushions: Constructed using 1" foam wrapped in fabric with concealed staples Back: Upholstered or wood back

Glides: Injection molded glides

#### Installation

No installation required

#### Warranty

10 year limited replacement warranty

#### Maintenance

Frame: Norix recommends the use of soap and water or cleaner made for stainless steel for both regular and deep cleaning.

Upholstery: Refer to upholstery manufacturer's cleaning instructions for specific fabric.

### TESTING

#### **Environmental Test Standards**

• GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

#### **Performance Test Standards**

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- Meets or exceeds the requirements of ANSI/BIFMA X5.4-2012
- Tested to 500 lb static load

# NORIX.COM