# Arcadian Open Chest





Model

ARC700

Weight

70 lbs / 31.8 kg

Dimensions	in	cm
Height	42"	106.7
Depth	18"	45.7
Width	30"	76.2
<b>Cubby Volume</b>	cu ft	m <sup>3</sup>
Top Cubby	0.78	0.02
Bottom Cubby	2.5	0.07

<sup>\*</sup>Note: Dimensional tolerances are +1% due to manufacturing process.

#### **Finishes**

See Design Guide for finish options.

# **Options**

Factory Ballasting (50 lbs / 22.7 kg)

\*Ballastable up to 50 pounds (22.7 kg) of dry sand or gravel. Factory ballasting option must be communicated at time of order; products are not field ballastable.

### Assembly

None required.

# **Fabrication & Material**

Rotationally molded high-impact polyethylene is specially formulated for superior durability and impact resistance. The seamless, one-piece construction has no internal openings for added safety and security. A slightly textured surface delivers long-term, maintenance-free performance. Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Made in the U.S.A.

## Warranty

10 year limited replacement warranty.

## Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. Arcadian products are bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

## Installation

Bolt-down kit required for floor anchoring. Proprietary anchoring system with concealed hardware intended for concrete floors and/or walls. (Please consult contractor or facility management as necessary.) Security caulk may be applied to the perimeter after anchoring.

## **Performance Test Standards**

• Product tested to 1,000 lbs (453.6 kg) static load.

#### **Environmental Test Standards**

 GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

## Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 116, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- ASTM E1537 Test Method for Fire testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture







<sup>\*</sup>Intended for indoor use only