

## SPECIFICATIONS



### Model

C920

### Weight

10 lbs

### Dimensions

Seat Height	17.3"
Overall Height	32"
Depth	23.2"
Width	19.7"

### COM Yards

Total Yards	1.2
Seat Yards	0.75
Back Yards	0.65

\*Intended for indoor use only



## DETAILS

### Finishes

See Design Guide for finish options.

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

### Optional Upholstery

View our upholstery selections at [www.norix.com/fabrics](http://www.norix.com/fabrics). Fabric Grade Levels: Grade B, Grade C, Grade D, Grade E, Grade F, Grade G, Grade H, COM.

### Assembly

None required

### Fabrication & Material

Ideal for staff use and monitored programming rooms. Not suitable for confined areas.

Seat shell: One-piece, injection-molded high-impact grade copolymer polypropylene.

Legs: Powder coated aluminum in the color black with friction fit foot caps.

### Installation

None required

### Warranty

10 year limited replacement warranty

### Maintenance

Seats: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. For the deep-scrub cleaning of tougher stains, marks and debris, we recommend the use of Clorox® Clean-Up® Cleaner + Bleach or an equivalent cleaning solution.

Legs: Norix recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of powder-coated aluminum.

Optional Upholstery: Refer to Upholstery Manufacturer's cleaning instructions.

## TESTING

### Performance Test Standards

- ANSI/BIFMA X5.1 2002 General Purpose Office Chairs
- ISO 14001:2015
- Tested to 500 lb static load

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.