



CA4200
(42" / 106.7 cm Round)

Model

CA4800
(48" / 121.9 cm Round)

CA4242
(42" / 106.7 cm Square)

Weight

89 lbs / 40.4 kg
(42" / 106.7 cm Round)

112 lbs / 50.8 kg
(48" / 121.9 cm Round)

92.5 lbs / 42 kg
(42" / 106.7 cm Square)

Finishes

See Design Guide for finish options.

Options

- Factory Ballasting (150 lbs / 68 kg)

**Ballastable up to 200 pounds (90.7 kg) of dry sand or gravel. On site ballast materials not supplied by Norix.*

Assembly

Refer to manufacturer's instructions for assembly.

**Intended for indoor use only*

CA4200 (42" Round)	in	cm
Diameter	42"	106.7
Height	30.5"	77.8
CA4800 (48" Round)	in	cm
Diameter	48"	121.9
Height	30.5"	77.5
CA4242 (42" Square)	in	cm
Width	42"	106.7
Depth	42"	106.7
Height	30.5"	77.5

Fabrication & Material

Base: One-piece, rotationally-molded polyethylene with lightly textured, maintenance-free surface which allows for easy cleaning. Specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability.

Laminate Top: Premium M3 Grade, 45 lb (20.4 kg) density particle board table top core is sandwiched between 1/8" (0.32 cm) thick hardboard and faced with special 0.05" (0.13 cm) thick high pressure laminate for superior quality and long term durability. Molded edge is radiused for safety and comfort, pressure fused to the top, rendering it firmly attached and highly sanitary. Embedded T-nuts secure top to base with tight steel-to-steel connection for maximum long term reliability. Robust 1.5" (3.8 cm) thick edge profile. Made in the U.S.A.

Warranty

10 year limited replacement warranty.

Maintenance

Top: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product.

Base: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

Installation

Ballast weighting required to validate warranty. Recommend 150 pounds (68.4 kg) of dry sand or gravel ballast. On site materials not supplied by Norix.

Performance Test Standards

- Product tested to 1,000 lbs (453.6 kg) static load.

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

