

## SPECIFICATIONS



Model		Dimensions		COM Yards	
FA		Seat Height	18.5"	Total Yards	8.5
<b>Weight</b>		Overall Height	32"	Seat Yards	1.75
Plinth Base	83 lbs	Depth	30"	Back Yards	1.25
Steel Base	91 lbs	Width	29.5"	Arm Yards	5.5
Rocker Base	91 lbs	Arm Height	26"		

\*Intended for indoor use only



## DETAILS

### Finishes

See Design Guide for finish options.

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

### Options

Ganging or Bolt-down.

Factory Ballasting (*Plinth Base only*) (50 lbs).

\*Ganging and Bolt-Down are not available for Rocker base.

\*\*Ballastable up to 50 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

### Upholstery

View our upholstery selections at [www.norix.com/fabrics](http://www.norix.com/fabrics). Fabric Grade Levels: Grade B-H and COM. Seat, arms and back are available in different fabrics. Upholstered flammability standard upgradeable to TB133.

### Fabrication & Material

Constructed of wood, 2.5" thick foam, enclosed wood panel with secure hardware and finished with upholstery. Optional plinth or steel base. Made in the U.S.A.

### Assembly

None required

### Installation

Required for Ganging plates and Bolt-down.

### Warranty

10 year limited replacement warranty.

### Maintenance

Refer to upholstery manufacturer's cleaning instructions for specific fabric.

## TESTING

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

### Performance Test Standards

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- Product tested to 750 lb static load
- Meets the requirements of ANSI/BIFMA X5.4-2012