

Forté®

Guest Arm Chair



Model FC600
Weight 28 lbs / 12.7 kg

Dimensions	in	cm
Seat Height	18.1"	46
Seat Width	18.6"	47.2
Overall Height	32.9"	83.6
Depth	26.3"	66.8
Width	24"	61
Arm Height	26.1"	66.3
Upholstery	yd	m
COM	1	0.9

*View our upholstery selection on our website.
Fabric Grades B - H and COM available.

Finishes

See Design Guide for finish options.

Options

- Upholstered Seat
- TB133 Upholstery Upgrade
- Bolt-Down Kit
- Ganging Kit
- Factory Ballasting (50 lbs / 22.7 kg)

*Ballastable up to 100 pounds (45.4 kg) of dry sand or gravel. On site ballast materials not supplied by Norix.

Assembly

None required.

Patents

Patents pending.

*Intended for indoor use only

Fabrication & Material

One-piece rotationally-molded polyethylene with lightly textured maintenance free surface which allows for easy cleaning. Tamper-resistant steel encased nylon glides for floor protection. Molded-in steel threaded inserts for optional ganging side-to-side and molded in access port with threaded screw cap for ballasting. High-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability. Made in the U.S.A.

Warranty

10 year limited replacement warranty.

Maintenance

Seats: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

Optional Upholstery: Refer to Upholstery Manufacturer's cleaning instructions.

Installation

Required for ganging plates.

Performance Test Standards

- Tested to 750 lbs (340.2 kg) static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18") (113.4 kg from 45.7 cm)

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards - Upholstered Chair

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies

Flammability Test Standards - Non-Upholstered Chair

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture
- UL94 HB Test for Flammability of Plastic Materials
- British Standard BS 7176: 2007, High Hazard Occupancy (BS EN 1012-1: 2006, BS EN 1012-2: 2006, BS 5852: 2006)

