



**Model** FC620/FC660

**Weight** 44 lbs / 20 kg

Dimensions	in	cm
Seat Height	18"	45.7
Seat Width	21.9"	55.6
Overall Height	32.6"	82.8
Depth	30.9"	78.5
Width	27"	68.6
Arm Height	26"	66
Upholstery	yd	m
COM	1.15	1.1

\*View our upholstery selection on our website.  
Fabric Grades B - H and COM available.

## Finishes

See Design Guide for finish options.

## Options

- Upholstered Seat
- TB133 Upholstery Upgrade
- Bolt-Down Kit
- Ganging Kit
- Factory Ballasting (50 lbs / 22.7 kg)

\*Ballastable up to 100 pounds (45.4 kg) of dry sand or gravel. On site ballast materials not supplied by Norix.

## Assembly

None required.

## Patents

Patents pending.

\*Intended for indoor use only

## Fabrication & Material

One-piece rotationally-molded polyethylene with lightly textured maintenance free surface allows for easy cleaning. Anti-ligature design with no internal openings. Molded-in steel threaded inserts for optional ganging side-to-side. Push in cap seals access port for ballasting. High-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability. Made in the U.S.A.

## Warranty

10 year limited replacement warranty.

## Maintenance

**Seats:** For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

**Optional Upholstery:** Refer to Upholstery Manufacturer's cleaning instructions.

## Installation

Required for ganging plates.

## Performance Test Standards

- Tested to 750 lbs (340.2 kg) static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18") (113.4 kg from 45.7 cm)

## Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

## Flammability Test Standards - Upholstered Chair

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies

## Flammability Test Standards - Non-Upholstered Chair

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture
- UL94 HB Test for Flammability of Plastic Materials
- British Standard BS 7176: 2007, High Hazard Occupancy (BS EN 1012-1: 2006, BS EN 1012-2: 2006, BS 5852: 2006)

