

## Occasional Table - Laminate Top with Molded Base



<b>Model</b>	FO
<b>Weight</b>	48 lbs / 21.8 kg

Dimensions	in	cm
Height	13.2"	371
Depth	27"	68.6
Width	27"	68.6

### Finishes

See Design Guide for finish options.

### Options

- Factory Ballasting (50 lbs / 22.7 kg)

\*Ballastable up to 100 pounds (45.4 kg) of dry sand or gravel. On site ballast materials not supplied by Norix.

### Assembly

None required.

\*Intended for indoor use only

### Fabrication & Material

**Top:** Decorative high pressure laminate is bonded to a core of 45 lb (20.4 kg) density particle board with embedded T-nuts for securing top to base. Polyurethane edge is radiused for safety and pressure fused to the top, rendering it firmly attached and highly sanitary. 1¾" (3.2 cm) thick edge profile.

**Base:** Specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ material is fully compounded for superior color consistency and durability. Molded-in steel threaded inserts for optional ganging side-to-side. Push in cap seals access port for sand or gravel ballast capability. Anti-ligature design with no internal openings. Made in the U.S.A.

### Warranty

10 year limited replacement warranty.

### Maintenance

**Top:** For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product.

**Base:** For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

### Installation

Required for ganging plates and ballast. Ballast weighting required to validate warranty. Recommend 100 pounds (45.4 kg) of dry sand or gravel. On site ballast materials not supplied by Norix.

### Performance Test Standards

- Tested to 1,000 lbs (453.6 kg) static load.

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

### Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture
- UL94 HB Test for Flammability of Plastic Materials

