

SPECIFICATIONS



Model	Dimensions	COM Yards
FV	Height 18.5"	Total Yards 2
Weight	Width 30"	Seat Yards 2
Plinth Base 49 lbs		
Steel Base 57 lbs		

*Intended for indoor use only



DETAILS

Finishes

See Design Guide for finish options.

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

Power (Max of 2), Ganging, and Bolt-down.
Factory Ballasting (*Plinth Base only*) (50 lbs).

*Ballastable up to 50 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

Upholstery

View our upholstery selections at www.norix.com/fabrics. Fabric Grade Levels: Grade B-H and COM. Seat, arms and back are available in different fabrics. Upholstered flammability standard upgradeable to TB133.

Fabrication & Material

Constructed of wood, 2.5" thick foam, enclosed wood panel with secure hardware and finished with upholstery. Optional plinth or steel base. Made in the U.S.A.

Top: 45 lb density M3 grade particle board with embedded T-nuts for mechanically attaching top to base with a secure steel-to-steel connection. Decorative high-pressure laminate. Made in the U.S.A.

Assembly

None required

Installation

Required for Ganging plates and Bolt-down.

Warranty

10 year limited replacement warranty.

Maintenance

Refer to upholstery manufacturer's cleaning instructions for specific fabric.

TESTING

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Performance Test Standards

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- Product tested to 750 lb static load
- Meets the requirements of ANSI/BIFMA X5.4-2012