

# **SPECIFICATIONS**



Model G20 Weight 72 lbs

**Dimensions**Overall Height

Overall Height 29.5" Overall Width 75.5" Depth 31.4"

Depth 31.4" Seat Height 15.8"

Designed by











### **DETAILS**

### **Finishes**

See Design Guide for finish options.

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

### **Options**

Bolt-Down Plates,

On site Ballasting (100 lbs)

\*Ballastable up to 100 lbs of dry sand and gravel. On site ballast materials not supplied by Norix.

## **Assembly**

None required

### Installation

None required

#### **Fabrication & Material**

One-piece, rotationally molded, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability. Enhanced UV resistant formulation suitable for both indoor and outdoor use. Rounded edges for added safety and adjustable removable glides to stabilize for un-even surfaces. Made in the U.S.A.

#### Warranty

5 year limited replacement warranty.

#### Maintenance

For routine and regular cleaning maintenance, Norix\* recommends the use of Simple Green\* or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex\*, Wexcide\* or Oxivir Five 16\*) per manufacturers' instructions.

## **TESTING**

# Performance Test Standards:

- Tested to 500 lb static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18")

### **Environmental Test Standards**

• GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

# Flammability Test Standards:

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test method for Fire Testing of Real Scale Upholstered Furniture Items