



Model PRD240
Weight 29 lbs / 13.2 kg

Dimensions	in	cm
Height	23.5"	59.7
Overall Length	20"	50.8
Overall Width	20"	50.8
Cubby Volume	cu ft	m ³
Top Cubby	0.86	0.02
Bottom Cubby	1.28	0.03

**Note: Dimensional tolerances are +1% due to manufacturing process.*

Finishes

See Design Guide for finish options.

Options

- Factory Ballasting (35 lbs / 15.9 kg)

**Factory ballasting option must be communicated at time of order; products are not field ballastable.*

Patents

Patents Pending

**Intended for indoor use only*

Fabrication & Material

One-piece, 100% seamless, specially formulated polymer construction is structurally reinforced for superior durability, impact resistance and security. Rounded edges for added safety. Each piece is uniquely fashioned with proprietary TruGrain™ polymer formulation to replicate natural wood, and deliver a residential, non-institutional appearance. The seamless, one-piece construction delivers long-term, maintenance-free performance superior to wood in infection-control, fluid, tamper, infestation, contraband resistance and ligature resistant design. Contains a minimum of 30% recycled content. Made in the U.S.A.

Warranty

10 year limited replacement warranty.

Maintenance

For routine and regular cleaning, Norix® recommends the use of Simple Green® or an equivalent cleaning product with a soft damp cloth. Prodigy® products are suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

Installation

Proprietary ligature resistant floor anchoring system with concealed hardware (mechanism and all anchoring hardware included). Anchoring mechanism and hardware intended for concrete floors. (Please consult contractor or facility management as necessary). Tamper-resistant non-removable steel encased floor glides are included and may be field installed. Security caulk may be applied to the perimeter after anchoring.

Performance Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Environmental Test Standards

- Tested to 1,000 lbs (453.6 kg) static load.

Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 116, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- ASTM E1537 Test Method for Fire testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture

