Toro

Lounge Arm Chair





Model

TOR₁₀

Weight

50 lbs / 22.7 kg

Dimensions	in	cm
Seat Height	18"	45.7
Seat Width	22"	55.9
Seat Depth	18"	45.7
Overall Height	31.2"	79.2
Overall Depth	27.5"	69.9
Overall Width	26"	66
Arm Height	23.6"	59.9
Upholstery	yd	m
COM Total	2.4	2.2
COM Seat	1	0.9
COM Back	1.4	1.3

^{*}View our upholstery selection on our website. Fabric Grades B - H and COM available.

Finishes

See Design Guide for finish options.

Options

- Replacement Cushions
- TB133 Upholstery Upgrade
- · Ganging kit
- Bolt-down kit
- Factory Ballasting (50 lbs / 22.7 kg)

Assembly

None required.

^{*}Intended for indoor use only











Fabrication & Material

Frame: One-piece, 100% seamless, specially formulated polymer construction is structurally reinforced for superior durability, impact resistance and security. Rounded edges for added safety. Each piece is uniquely fashioned with proprietary TruGrain™ polymer formulation to replicate natural wood, and deliver a residential, non-institutional appearance. The seamless, one-piece construction delivers long-term, maintenance-free performance superior to wood in infection-control, fluid, tamper, infestation and contraband resistance. Contains a minimum of 30% recycled content. Made in the U.S.A.

Back: 5" (12.7 cm) polyurethane foam is fully upholstered and stapled to high strength plywood. Plywood is connected to the frame with tamper-resistant hardware and embedded steel T-nuts for a secure steel-to-steel connection. **Seat**: Upholstered 4" (10.2 cm) polyurethane foam with a 6" (15.2 cm) bullnose glued to high strength plywood. Plywood is connected to the frame with tamper-resistant hardware and embedded steel T-nuts for a secure steel-to-steel connection. The seat features both a side and back clean-out for easy cleaning. Made in the U.S.A.

Warranty

10 year limited replacement warranty.

Maintenance

Frame: For routine and regular cleaning, Norix® recommends the use of Simple Green® or an equivalent cleaning product with a soft damp cloth. Prodigy® products are suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

Upholstery: Refer to upholstery manufacturer's cleaning instructions.

Performance Test Standards

- Tested to 750 lbs (340.2 kg) static load.
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18") (113.4 kg from 45.7 cm)

Environmental Test Standards

• GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards

Optional upgrade for compliance with the following standards:

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items

^{*}Ballastable up to 50 pounds (22.7 kg) of dry sand or gravel. On site ballast materials not supplied by Norix.