

SPECIFICATIONS



Model

WC10

Weight

42 lbs

*Intended for indoor use only

Dimensions

Seat Height	18.5"
Seat Width	22"
Overall Height	31.4"
Depth	18.7"
Overall Width	26"
Arm Height	25.4"

COM Yards

Total Yards	2.4
Seat Yards	1
Back Yards	1.4



DETAILS

Finishes

See Design Guide for finish options.

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

Ganging kit, Bolt-down kit
Factory Ballasting (50 lbs)

*Ballastable up to 50 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

Replacement cushions are available and easily installed in the field. Seat and backs are available in different fabrics. Upholstered flammability standard upgradeable to TB133.

Upholstery

View our upholstery selections at www.norix.com/fabrics. Fabric Grade Levels: Grade B, Grade C, Grade D, Grade E, Grade F, Grade G, Grade H, COM.

Assembly

None required

Installation

Required for ganging plates.

Fabrication & Material

Frame: One-piece rotationally-molded polyethylene with lightly textured surface allows for easy cleaning. Specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading) is chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability. Molded-in access port with threaded screw cap for ballast weighting capability. Non-removable steel encased nylon glides for floor protection.

Back: 5" polyurethane foam is fully upholstered and stapled to high strength plywood. Plywood is connected to the frame with tamper-resistant hardware and embedded steel T-nuts for a secure steel-to-steel connection.

Seat: Upholstered 4" polyurethane foam with a 6" bullnose glued to high strength plywood. Plywood is connected to the frame with tamper-resistant hardware and embedded steel T-nuts for a secure steel-to-steel connection. The seat features both a side and back clean-out for easy cleaning. Made in the U.S.A.

Warranty

10 year limited replacement warranty

Maintenance

Frame: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

Upholstery: Refer to upholstery manufacturer's cleaning instructions.

TESTING

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards

Optional upgrade for compliance with the following standards:

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items

Performance Test Standards

- Tested to 750 lb static load
- Meets or exceeds the requirements of ANSI/BIFMA X5.4-2012