



| | |
|---------------|------------------|
| Model | ATN102 |
| Weight | 66 lbs / 29.9 kg |

| Dimensions | in | cm |
|------------|-------|-------|
| Width | 83.5" | 212.1 |
| Depth | 39.5" | 100.3 |
| Height | 8.5" | 21.6 |

*Note: Dimensional tolerances are +1% due to manufacturing process.

Finishes

See Design Guide for finish options.

Options

- Bolt-Down

Assembly

None required.

*Intended for indoor use only

Fabrication & Material

Slightly textured maintenance free surface allows for easy cleaning. Rotationally molded, ligature resistant, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Anti-ligature design with no internal openings. Premium TruColor™ material is fully compounded for superior color consistency and durability. Made in the U.S.A.

*For use with ATN101 and ATN101B only.

Warranty

10 year limited replacement warranty.

Norix recommends products placed in storage prior to installation should be held in a climate controlled area similar to the room where the product will be used. Norix also recommends that any Attenda® products shipped via ocean container maintain a temperature of 70-75°F (21.1-23.9°C) with a Relative Humidity of 35%.

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. Attenda® products are bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions. Norix recommends inspecting fasteners after each use of the restraints, along with regular monthly inspections. Bolt-down fasteners should be tight with no gaps larger than 1/16" (0.2 cm) between the bottom of the bed and the floor. There should be no visible cracks in the caulk, if applied.

Installation

Norix supplied tamper resistant hardware bolts into Riser through existing mounting holes in Attenda® Bed. Riser can be sand ballasted through knock-out access port for weighting free standing units. Push in cap seals access port.

Patents

This product may be covered by US Patent Nos. US 8,007,059 B2.

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture

