

Attenda®

Space-Saver Bed



Model ATN120
Weight 80 lbs / 36.3 kg

Dimensions	in	cm
Overall Length	79"	200.7
Overall Width	31"	78.7
Height	15"	38.1
Bed Deck Length	77"	195.6
Bed Deck Width	29"	73.7

Note: Dimensional tolerances are +1% due to manufacturing process.

Mattress Size

29"x77" (73.7x195.6 cm)

Finishes

See Design Guide for finish options.

Options

- **ATN123:** Space-Saver with no Mounting Holes

Assembly

None Required.

*Intended for indoor use only



Fabrication & Material

Slightly textured maintenance free surface allows for easy cleaning. Rotationally molded, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Ligature resistant design with no internal openings. Premium TruColor™ material is fully compounded for superior color consistency and durability. Unit is filled with rigid polyurethane foam for increased durability and sound absorption. Made in the U.S.A.

Warranty

10 year limited replacement warranty.

Norix recommends products placed in storage prior to installation should be held in a climate controlled area similar to the room where the product will be used. Norix also recommends that any Attenda® products shipped via ocean container maintain a temperature of 70-75°F (21.2-23.9°C) with a Relative Humidity of 35%.

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. Attenda® products are bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions. Norix recommends inspecting fasteners after each use of the restraints, along with regular monthly inspections. Bolt-down fasteners should be tight with no gaps larger than 1/16" (0.2 kg) between the bottom of the bed and the floor. There should be no visible cracks in the caulk, if applied.

Installation

Wedge anchors and 3/8" (0.95 cm) bolts required for permanently attaching to floor. Anchors and bolts not supplied by Norix. Groove along underside edge for caulk application (caulk not supplied by Norix).

Patents

This product may be covered by US Patent Nos. US 8,007,059 B2, and US 10,507,150 B2.

Performance Test Standards

- Product tested to 1,000 lbs (453.6 kg) static load.

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture