

# Attenda®

## 13" Sleigh Bed



<b>Model</b>	ATN140
<b>Weight</b>	125 lbs / 56.7 kg

<b>Dimensions</b>	<b>in</b>	<b>cm</b>
Overall Length	92.8"	235.7
Overall Width	38.5"	97.8
Height	25.4"	64.5
Surface Height	13"	33.1

Note: Dimensional tolerances are +1% due to manufacturing process.

### Mattress Size

36"x80" (91.4x203.2 cm)

### Finishes

See Design Guide for finish options.

### Options

- Bolt-down Kit
- **ATN140H:** Drainage holes

### Assembly

None required.

\*Intended for indoor use only

### Fabrication & Material

Slightly textured maintenance free surface allows for easy cleaning. Rotationally molded, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ material is fully compounded for superior color consistency and durability. Unit is filled with rigid polyurethane foam for increased durability and sound absorption. Made in the U.S.A.

### Warranty

10 year limited replacement warranty.

Norix recommends products placed in storage prior to installation should be held in a climate controlled area similar to the room where the product will be used. Norix also recommends that any Attenda® products shipped via ocean container maintain a temperature of 70-75°F (21.1-23.9°C) with a Relative Humidity of 35%.

### Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. Attenda® products are bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions. Norix recommends inspecting fasteners after each use of the restraints, along with regular monthly inspections. Bolt-down fasteners should be tight with no play between the bolt-down bracket and the floor on the anchored side of the bed.

### Installation

Required for Bolt-down Kit.

### Patents

This product may be covered by US Patent Nos. US 8,635,722B2.

### Performance Test Standards

- Product tested to 1,000 lb (453.6 kg) static load.

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

### Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture

