



### Model

VFB1-1 (Single Seat)  
VFB0-1 (Add-On)

### Weight

45 lbs / 20.4 kg (Single Seat)  
37 lbs / 16.8 kg (Add-On)

Dimensions	in	cm
Seat Height	18"	45.7
Seat Width	17"	43.2
Seat Depth	16"	40.6
Overall Height	31.5"	80
Overall Depth	25"	63.5
Arm Height	24"	61

### Finishes

See Design Guide for finish options.

### Options

- Non-Removable Glides
- Bolt-Down Kit
- Add on Unit (VFB0-1)
- Cuff Rings

### Assembly

VersaFrame™ ships flat-packed and requires assembly. Refer to manufacturer's instructions for assembly.

*\*Intended for indoor use only*

### Fabrication & Material

**Base Frame:** Square tube steel, bent and welded to provide modular, in-line seating. Flat steel plate welded to the frame at each seat location to provide strength, support, and a mounting platform on which the seat is attached. 16 gauge steel tube with 14 gauge steel seat plates with ¼" (0.6 cm) bend.

**Seats:** One-piece seat and back. Smooth maintenance free surface allows for easy cleaning. Molded-in threaded steel inserts provide for tamper resistant attachment to base frame. Rotationally molded, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability.

### Warranty

10 year limited replacement warranty.

### Maintenance

**Frame:** Norix recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of powder coated steel.

**Seats:** For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

### Installation

For bolt-down application, fasten to floor. Floor mounting hardware included.

### Performance Test Standards

- Product tested to 1,000 lbs (453.6 kg) static load
- Product dynamic drop tested to a relative impact force of two times ANSI/BIF-MAX 5.4 15.4.2012 (250 lbs. from 18") (113.4 kg from 45.7 cm)

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

### Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture

