



**Model**

PRD801 (Door)

PRD804 (No Door)

**Weight**

200 lbs / 90.7 kg (Door)

155 lbs / 70.3 kg (No Door)

Dimensions	in	cm
Overall Length	24"	61
Overall Width	24"	61
Overall Height	78"	198.1

*\*Note: Dimensional tolerances are +1% due to manufacturing process.*

**Finishes**

See Design Guide for finish options.

**Options PRD801 (Door)**

- Left or Right Hinge

*\*Wardrobe door cannot be installed post manufacturing, must be specified at time of order.*

*\*Lock comes standard.*

**Patents**

Patents Pending

*\*Intended for indoor use only*

**Fabrication & Material**

One-piece, 100% seamless, specially formulated polymer construction is structurally reinforced for superior durability, impact resistance and security. Rounded edges for added safety. Each piece is uniquely fashioned with proprietary TruGrain™ polymer formulation to replicate natural wood, and deliver a residential, non-institutional appearance. The seamless, one-piece construction delivers long-term, maintenance-free performance superior to wood in infection-control, fluid, tamper, infestation and contraband resistance. Contains a minimum of 30% recycled content. Made in the U.S.A.

**Warranty**

10 year limited replacement warranty.

**Maintenance**

For routine and regular cleaning, Norix® recommends the use of Simple Green® or an equivalent cleaning product with a soft damp cloth. Prodigy® products are suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

**Installation**

Proprietary ligature resistant floor and wall anchoring system with concealed hardware (the anchoring mechanisms are included, the anchoring hardware is NOT included). Please consult contractor or facility management as necessary. Security caulk may be applied to the perimeter after anchoring.

**Environmental Test Standards**

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG

**Flammability Test Standards**

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 116, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- ASTM E1537 Test Method for Fire testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture

