Attenda

Nightstand





Model ATN250

30 lbs / 13.6 kg (Standard) Weight 33 lbs / 15 kg (Deluxe)

Dimensions	in	cm
Width	22"	55.9
Depth	22"	55.9
Height (Standard)	23.3"	59.2
Height (Deluxe)	24"	61

^{*}Note: Dimensional tolerances are +1% due to manufacturing process.

Finishes

See Design Guide for finish options.

Options

- ATN250: Standard Nightstand
- ATN255: Deluxe Nightstand
- ATN253B35: Ballasted* Standard Nightstand (35 lbs / 15.9 kg)
- ATN255B: Ballasted* Deluxe Nightstand (35 lbs / 15.9 kg)

Assembly

None required.

Fabrication & Material

Base: Slightly textured, maintenance-free surface allows for easy cleaning. Rotationally molded, specially formulated, ligature resistant, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Anti-ligature design with no internal openings. Premium TruColor™ material is fully compounded for superior color consistency and durability. Unit is filled with rigid polyurethane foam for increased durability and sound absorption.

Optional Laminate Top: 45 lb (20.4 kg) density M3 grade particle board with embedded T-nuts for mechanically attaching top to base with a secure steelto-steel connection. Decorative high-pressure laminate sealed with a specially formulated, highly durable molded edge. Edge is radiused for safety and pressure fused to the top, making it highly sanitary. Made in the U.S.A.

Warranty

10 year limited replacement warranty.

Norix recommends products placed in storage prior to installation should be held in a climate controlled area similar to the room where the product will be used. Norix also recommends that any Attenda® products shipped via ocean container maintain a temperature of 70-75°F (21.1-23.9°C) with a Relative Humidity of 35%.

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. Attenda® products are bleach/ water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

Installation

Anchors required for permanently attaching to floor. Anchors not supplied by Norix. Groove along mounting surface for caulk application (caulk not supplied by Norix).

Patents

This product may be covered by US Patent No. US 8,007,059 B2.

Environmental Test Standards

• GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818, UL.COM/GG.

Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture







^{*}Ballastable up to 35 pounds (15.9 kg) of dry sand or gravel. Factory ballast cannot be installed on site

^{*}Intended for indoor use only