



Model	Weight		Top Size		Height	
	lbs	kg	in	cm	in	cm
EV3600	74	33.6	36" Diameter	91.4 Diameter	31.1"	79
EV3636	85	38.6	36"x36"	91.4x91.4		
EV4200	88	39.9	42" Diameter	106.7 Diameter		
EV4242	104	47.2	42"x42"	106.7x106.7		
EV4800	106	48.1	48" Diameter	121.9 Diameter		

Finishes

See Design Guide for finish options.

Options

- Bolt-Down
- Factory Ballasting (200 lbs / 90.7 kg)

*Ballastable up to 200 lbs (90.7 kg) of dry sand or gravel. On site ballast materials not supplied by Norix.

Assembly

Refer to manufacturer's instructions for assembly.

*Intended for indoor use only

Fabrication & Material

Base: One-piece, rotationally-molded polyethylene, maintenance-free surface which allows for easy cleaning. Specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability.

Laminate Top: Premium M3 Grade, 45 lb. (20.4 kg) density particle board table top core is sandwiched between 1/8" (0.3 cm) thick hardboard and faced with special 0.05" (0.1 cm) thick high pressure laminate for superior quality and long term durability. Molded edge is radiused for safety and comfort, pressure fused to the top, rendering it firmly attached and highly sanitary. Embedded T-nuts secure top to base with tight steel-to-steel connection for maximum long term reliability. Robust 1.5" (3.8 cm) thick edge profile.

Made in the U.S.A.

Warranty

10 year limited replacement warranty.

*To validate warranty, this product is required to be secured with a bolt-down kit or ballasted with recommended 200 lbs (90.7 kg) of sand. Ballasting sand is not supplied by Norix. For complete warranty information, please refer to our Warranty Policy.

Maintenance

Top: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product.

Base: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

Installation

Ballast weighting required to validate warranty. Recommend 200 lbs (90.7 kg) of dry sand or gravel ballast. On site materials not supplied by Norix.

Performance Test Standards

- Product tested to 1,000 lbs (453.6 kg) static load.

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies.
- ASTM E1537 Test method for Fire Testing of Real Scale Upholstered Furniture Items

