



**Model** FT600

**Weight** 31 lbs / 14.1 kg

Dimensions	in	cm
Height	29.2"	74.2
Diameter	36"	91.4

## Finishes

See Design Guide for finish options.

## Options

- Factory Ballasting (150 lbs / 68 kg)

*\*Ballastable up to 200 pounds (90.7 kg) of dry sand or gravel. On site ballast materials not supplied by Norix.*

## Assembly

Refer to manufacturer's instructions for assembly.

*\*Intended for indoor use only*

## Fabrication & Material

One-piece, rotationally-molded polyethylene with lightly textured, maintenance-free surface which allows for easy cleaning. Specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability. Made in the U.S.A.

## Warranty

10 year limited replacement warranty.

*\*To validate warranty, this product is required to be secured with a bolt-down kit or ballasted with recommended 150 lbs (68 kg) of sand. Ballasting sand is not supplied by Norix. For complete warranty information, please refer to our Warranty Policy.*

## Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

## Installation

Ballast weighting required to validate warranty. Recommend 150 pounds (68 kg) of dry sand or gravel ballast. On site materials not supplied by Norix.

## Performance Test Standards

- Product tested to 1,000 lbs (453.6 kg) static load.

## Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

## Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies.
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies.
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture
- UL94 HB Test for Flammability of Plastic Materials

