

# Kube

## Right Arm Chair



<b>Model</b>	KE12R
<b>Weight</b>	24 lbs / 10.9 kg

<b>Dimensions</b>	<b>in</b>	<b>cm</b>
Arm Height	21"	53.3
Seat Height	16"	40.6
Seat Depth	20"	50.8
Overall Depth	28"	71.1
Overall Width	28"	71.1
Overall Height	29"	73.7
<b>Upholstery</b>	<b>yd</b>	<b>m</b>
COM	2.75	2.5

\*View our upholstery selection on our website.  
Fabric Grades C - L and COM available.

### Finishes

See Design Guide for finish options.

### Options

- Bolt-Down
- Ganging Kit
- On site Ballasting (50 lbs / 22.7 kg)

\*Ballastable up to 50 lbs (22.7 kg) of dry sand or gravel. On site ballast materials not supplied by Norix.

### Assembly

None required.

### Patents

Patents Pending.

### Fabrication & Material

**Base:** Strong, one-piece rotationally-molded polyethylene with lightly textured surface allows for easy cleaning. Adjustable removable glides to stabilize for uneven surfaces.

**Cushion:** 2" (5.1 cm) thick open cell foam adhered to EPP high density flexible foam is attached to base with heavy duty velcro.

### Warranty

5 year limited replacement warranty.

### Maintenance

**Base:** For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. For the deep-scrub cleaning of tougher stains, marks and debris, we recommend the use of Clorox® Clean-Up® Cleaner + Bleach or an equivalent cleaning solution.

**Seat:** Refer to upholstery manufacturer's cleaning instructions for specific fabrics.

### Performance Test Standards

- Tested to 500 lb (226.8 kg) static load.

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

