

Kube Table



Model KE50

Weight 17 lbs

Dimensions	in	cm
Height	12.1"	30.7
Depth	28"	71.1
Width	28"	71.1

Finishes

See Design Guide for finish options.

Options

- Bolt-Down
- Ganging Kit
- On site Ballasting (50 lbs / 22.7 kg)

**Ballastable up to 50 lbs (22.7 kg) of dry sand or gravel. On site ballast materials not supplied by Norix.*

Assembly

None required.

Patents

Patents Pending.

Fabrication & Material

Strong, one-piece rotationally-molded polyethylene with lightly textured surface allows for easy cleaning. Adjustable removable glides to stabilize for un-even surfaces.

Warranty

5 year limited replacement warranty.

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. For the deep-scrub cleaning of tougher stains, marks and debris, we recommend the use of Clorox® Clean-Up® Cleaner + Bleach or an equivalent cleaning solution.

Performance Test Standards

- Tested to 500 lb (226.8 kg) static load.

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

