

Leg Style Table



Model	Weight		Top Size		Height	
	lbs	kg	in	cm	in	cm
LS3636	107-115	48.5-52.2	36"x36"	91.4x91.4	29"	73.7
LS3072	124-142	56.2-64.4	30"x72"	76.2x182.9		
LS4242	121-137	54.9-62.1	42"x42"	106.7x106.7		
LS3096	166-190	75.3-86.2	30"x96"	76.2x243.8		
LS4800	122-138	55.3-62.6	48" Diameter	121.9		

Finishes

See Design Guide for finish options.

Options

- 2½" or 4" (6.4 or 10.2 cm) diameter Legs
- Bolt-Down

Assembly

Refer to manufacturer's instructions for assembly.

**Intended for indoor use only*

Fabrication & Material

Legs: Steel tubing welded to steel plate for attaching top. Bottom of leg sealed by means of a fully welded inset threaded to accommodate a tamper-resistant adjustable leveling glide. 2½" or 4" (6.4 or 10.2cm) diameter, 14 gauge wall thickness steel tubing welded to a 6" x 6" x ¼" (15.2 x 15.2 x 0.6cm) steel plate.

Top: Premium M3 Grade, 45 lb. (20.4 kg) density particle board table top core is sandwiched between ⅛" (0.3 cm) thick hardboard and faced with special 0.05" (0.1 cm) thick high pressure laminate for superior quality and long term durability. Molded edge is radiused for safety and comfort, pressure fused to the top, rendering it firmly attached and highly sanitary. Embedded T-nuts secure top to base with tight steel to steel connection for maximum long term reliability. Robust 1.5" (3.8 cm) thick edge profile. Made in the U.S.A.

Warranty

10 year limited replacement warranty.

Maintenance

Laminate Tops: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product.

Legs: Norix recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of steel.

Installation

None required.

Performance Test Standards

- Product tested to 1,000 lbs (453.6 kg) static load.

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

