

Comfort Shield® Custody Mattress

Norix Blue



Finishes

See Design Guide for finish options.

Options

- Mattress is available without integrated pillow

Assembly

Shipped assembled in poly bag.

**Intended for indoor use only*

Models	Weight		Dimensions		Height	
	lbs	kg	in	cm	in	cm
MCB4-2567	11.5	5.2	25" x 67"	63.5 x 170.2	4.5"	11.4
MCB4-2575	13	5.9	25" x 75"	63.5 x 190.5		
MCB4-2580	14	6.4	25" x 80"	63.5 x 203.2		
MCB4-2775	14	6.4	27" x 75"	68.6 x 190.5		
MCB4-2780	15	6.8	27" x 80"	68.6 x 203.2		
MCB4-2977	15.5	7.0	29" x 77"	73.7 x 195.6		
MCB4-3075	16	7.3	30" x 75"	76.2 x 190.5		
MCB4-3079	16.5	7.5	30" x 79"	76.2 x 200.7		
MCB4-3080	17	7.7	30" x 80"	76.2 x 203.2		

Note: Dimensional tolerances are +/- one inch.

Fabrication & Material

Sealed Seam Mattress with Integrated Double-Sided Pillow

11 oz/sq. ft. densified polyester fiber core with an integrated double sided pillow is encased in a fire retardant, polyurethane coated cover with radio frequency welded seams for enhanced hygiene, security and durability. Mattress is fluid, crack, peel, abrasion and bed bug resistant, anti-microbial and anti-fungal. Provides a virus barrier and is resistant to delaminating for greater infection control. Features a breathable vent that repels oil, water, blood, urine and other fluids. Core is made of non-hazardous materials. Made in the U.S.A.

Warranty

5 year limited prorated warranty against seam failure and cover material cracking. (Full warranty details available upon request.)

Maintenance

- Use hospital-grade cleaner or bleach/water solution on the entire mattress.
- Completely rinse with clean water (do not submerge).
- After cleaning, dry the mattress cover thoroughly. Do not place wet mattress onto a sleep surface; moisture may cause cover fabric damage (not covered by Limited Warranty).
- Contact Norix Customer Service for a mattress patch kit to address minor punctures and tears.

Performance Test Standards

- Tested to ASTM F1566 Hexagonal Roller Mattress Durability Test
- Tested to ASTM D751 Hydrostatic Resistance Test for Coated Fabrics

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards

- 16 CFR Part 1633
- 16 CFR Part 1632
- California Technical Bulletin 129

