# Comfort Shield® Dorm Mattress

## Innerspring

**Finishes** 

**Options** 

**Assembly** 





See Design Guide for finish options.

· Mattress is available without

Shipped assembled in poly bag.

integrated pillow

\*Intended for indoor use only

Models	Weight		Dimensions		Height	
	lbs	kg	in	cm	in	cm
MNE7-3675	28	12.7	36" x 75"	91.4 x 190.5	7"	17.8
MNE7-3680	28	12.7	36" x 80"	91.4 x 203.2		
MNE7-5480	33	15	54" x 80"	137.2 x 203.2		

Note: Dimensional tolerances are +/- one inch.

#### Fabrication & Material

Sewn Seam Mattress

1.35 pcf (pounds per cubic foot) density convoluted foam offers plush comfort on one side while 1.5 pcf foam yields a more firm sleep surface on the other. A premium weight, polyurethane side rail surrounds the tempered high carbon steel wire innerspring unit and is protected by a spun-bonded polypropylene quilt cover. The 210 Denier Oxford Nylon mattress cover with laminated fire retardant (FR) barrier and polyurethane coating is moisture resistant, anti-bacterial, anti-fungal, crack resistant, stain resistant, anti-static and breathable. Anti-crevice inverted seam uses FR Kevlar® thread for strength and durability. Made in the USA.

### Warranty

3 year limited replacement warranty.

#### Maintenance

- Use hospital-grade cleaner or bleach/water solution on the entire mattress.
- Completely rinse with clean water (do not submerge).
- After cleaning, dry the mattress cover thoroughly. Do not place wet mattress onto a sleep surface; moisture may cause cover fabric damage (not covered by Limited Warranty).
- Contact Norix Customer Service for a mattress patch kit to address minor punctures and tears.

### **Environmental Test Standards**

• GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

## Flammability Test Standards

- CPSC 16 CFR 1633
- California Technical Bulletin #129
- California Technical Bulletin #603
- ASTM E 1590
- ACSC 1632/D.O.C. (FF 4-72)
- Boston Fire Department BFD IX-11

