

Multi-Purpose Table



Finishes

See Design Guide for finish options.

Assembly

Refer to manufacturer's instructions for assembly.

**Intended for indoor use only*

T-Base Models	Weight		Top Size		Height	
	lbs	kg	in	cm	in	cm
MP1860	59	26.8	18"x60"	45.7x152.4	29"	73.3
MP2460	74	33.6	24"x60"	61x152.4		
MP3060	91	41.3	30"x60"	76.2x152.4		

X-Base Models	Weight		Top Size		Height	
	lbs	kg	in	cm	in	cm
MP3600	53	24	36" Diameter	91.4 Diameter	29"	73.7
MP3636	63	28.6	36"x36"	91.4x91.4		
MP4200	66	29.9	42" Diameter	106.7 Diameter		
MP4242	79	35.8	42"x42"	106.7x106.7		

Fabrication & Material

Base: 1 $\frac{3}{4}$ " (4.4 cm) 12 gauge steel tubes, fully welded and sealed on exposed ends. Glides adjust for leveling, but are tamper resistant as a security precaution. Factory, powder coated for optimum scratch and corrosion resistance.

Top: 45 lb (20.4 kg) density M3 grade particle board with embedded T-nuts sandwiched with decorative laminate and backer sheet. Edge is routed to receive glued and pinned black vinyl T-molding. 1 $\frac{1}{4}$ " (3.2 cm) thick edge profile. Made in the U.S.A.

Warranty

10 year limited replacement warranty.

Maintenance

Laminate Tops: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product.

Base: Norix recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of powder-coated seal.

Installation

None required.

Performance Test Standards

- Product tested to 500 lb (226.8 kg) static load.

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

