Tabla

Premium Drum Tables





Finishes

See Design Guide for finish options.

Options

- Bolt-down
- Factory Ballasting (50 lbs / 22.7 kg)
- *Ballasting must be communicated at time of order
- *TA1800-MC Ballastable up to 50 pounds (22.7 kg) of dry sand or gravel.
- *TA3600-MC Ballastable up to 100 pounds (45.4 kg) of dry sand or gravel.

Assembly

None required.

*Intended for indoor use only

Model	Weight		Top Size		Height	
	lbs	kg	in	cm	in	cm
TA1800-MC (Small)	30	13.6	18" Diameter	45.7 Diameter	18"	45.7
TA3600-MC (Large)	86	39	36" Diameter	91.4 Diameter		

Fabrication & Material

Fully wrapped laminate tables with internal rib structure for added strength and durability. Molded edge is pressure fused to the top, rendering it permanently affixed and pick resistant. Ballastable molded plinth base protects against scratches and chips. Anti-ligature design with no internal openings. Made in the U.S.A.

Warranty

10 year limited replacement warranty.

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product.

Performance Test Standards

• Product tested to 750 lbs (340.2 kg) static load.

Environmental Test Standards

 GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

