

# Tabla

## Basic Drum Table



Model	Weight		Top Size		Height	
	lbs	kg	in	cm	in	cm
TA1800 (Small)	25	11.3	18" Diameter	45.7 Diameter	18"	45.7
TA3600 (Large)	75	34	36" Diameter	91.4 Diameter		

### Finishes

See Design Guide for finish options.

### Options

- Bolt-down
- Factory Ballasting (50 lbs / 22.7 kg)

*\*TA1800 Ballastable up to 50 pounds (22.7 kg) of dry sand or gravel. On site ballast materials not supplied by Norix.*

*\*TA3600 Ballastable up to 100 pounds (45.4 kg) of dry sand or gravel. On site ballast materials not supplied by Norix.*

### Assembly

None required.

*\*Intended for indoor use only*

### Fabrication & Material

Fully wrapped laminate tables with internal rib structure for added strength and durability. Ligature resistant design with no internal openings. Made in the U.S.A.

### Warranty

10 year limited replacement warranty.

### Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product.

### Performance Test Standards

- Product tested to 750 lbs (340.2 kg) static load.

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

