

X-Base Table



| Model | Weight | | Top Size | | Height | |
|--------|--------|------|--------------|----------------|--------|------|
| | lbs | kg | in | cm | in | cm |
| XB3600 | 126 | 57.2 | 36" Diameter | 91.4 Diameter | 29.3" | 74.4 |
| XB3636 | 139 | 63 | 36"x36" | 91.4x91.4 | | |
| XB4200 | 142 | 64.4 | 42" Diameter | 106.7 Diameter | | |
| XB4242 | 162 | 73.5 | 42"x42" | 106.7x106.7 | | |
| XB4800 | 164 | 74.4 | 48" Diameter | 121.9 Diameter | | |

Finishes

See Design Guide for finish options.

Options

- 1¼" (3.2 cm) thick laminate top with black vinyl T-mold edge

Assembly

Refer to manufacturer's instructions for assembly.

**Intended for indoor use only*

Fabrication & Material

Base: Two interlocking base panels. 1½" (4.1 cm) thick 45 lb (20.4 kg) density particle board, sandwiched between ¼" (0.3 cm) thick hardboard and faced both sides with 0.05" (0.1 cm) thick, high-pressure laminate and banded on three exposed edges with heavy duty T-molding that is glued and steel pinned every twelve inches. An intermediate mounting plate joins the base to the top.

Top: Premium M3 Grade, 45 lb. (20.4 kg) density particle board table top core is sandwiched between ¼" (0.3 cm) thick hardboard and faced with special 0.05" (0.1 cm) thick high pressure laminate for superior quality and long term durability. Molded edge is radiused for safety and comfort, pressure fused to the top, rendering it firmly attached and highly sanitary. Embedded T-nuts secure top to base with tight steel to steel connection for maximum long term reliability. Robust 1.5" (3.8 cm) thick edge profile.

Made in the U.S.A.

Warranty

10 year limited replacement warranty.

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product.

Installation

None required.

Performance Test Standards

- Product tested to 1,000 lb (453.6 kg) static load.

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

