



Model EV4242-DF

Weight 55 lbs / 24.9 kg

Dimensions	in	cm
Width	42"	106.7
Depth	42"	106.7
Height	31.1"	79

Finishes

See Design Guide for finish options.

Options

- Bolt-Down
- Concealment Plate

**Indoor use only.*

- Factory Ballasting (200 lbs / 90.7 kg)

**Ballastable up to 200 lbs (90.7 kg) of dry sand or gravel. On site ballast materials not supplied by Norix.*

Assembly

Refer to manufacturer's instructions for assembly.

Fabrication & Material

Base: One-piece, rotationally-molded polyethylene, maintenance-free surface which allows for easy cleaning. Specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability.

DuoForm™ Top: Specially formulated, high-impact polyethylene layers with ultraviolet light stabilizers are permanently fused to offer enhanced strength and long-term durability. The molded, maintenance-free surface is easy to clean and chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability. The top and base are fastened using rivnuts to establish a highly secure, steel-to-steel connection. Precision-crafted 1.5" (3.8 cm) thick edge profile. Made in the U.S.A.

Warranty

5 year limited replacement warranty.

**To validate warranty, this product is required to be secured with a bolt-down kit or ballasted with recommended 200 lbs (90.7 kg) of sand. Ballasting sand is not supplied by Norix. For complete warranty information, please refer to our Warranty Policy.*

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcid® or Oxivir Five 16®) per manufacturers' instructions.

Installation

Ballast weighting required to validate warranty. Recommend 200 lbs (90.7 kg) of dry sand or gravel ballast. On site materials not supplied by Norix.

Performance Test Standards

- Product tested to 1,000 lbs (453.6 kg) static load.

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies.
- ASTM E1537 Test method for Fire Testing of Real Scale Upholstered Furniture Items

