

# Respite™

## Chaise Lounge



### Fabrication & Material

Premium TruColor™ polymer is fully compounded for superior color consistency and durability. One-piece rotationally molded, 0.25" (0.63 cm) flexible polyvinyl chloride exterior skin with softer durometer for a comfortable sit. Filled with flexible 2 part water-based polyurethane foam then attached with tamper resistant fasteners to a LLDPE (linear low density polyethylene) base. Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Ligature resistant design with no internal openings. Made in the U.S.A.

### Warranty

10 year limited replacement warranty.

*Certain apparel dyes, including indigo dyes commonly used in denim jeans, may migrate onto the surface of the material and become visible on lighter colors. This phenomenon is increased by humidity and temperature and may be irreversible. Certain inks, including ball point ink and permanent markers can create permanent stains.*

### Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Purple Power® Cleaner, a product that is readily available online and in stores that sell cleaning supplies. For the deep-scrub cleaning of tougher stains, marks and debris – including denim stains when cleaned often and soon after the dye appears – we recommend the use of World's Best Sensitive Surface Graffiti Remover. Removing stains and marks immediately or as soon as possible will produce the best results. Depending on the frequency the furniture is used, we also recommend standardized weekly surface cleanings with a soft cloth soaked in mild detergent and warm water. Finish with a wet cloth to remove dirt and dry with a soft cloth. Additionally, we recommend applying a thin layer of Black Magic Protectant every two months or after heavy stain cleaning to prevent accidental spills and stain penetration. Wipe chairs with foam sponge.

### Performance Test Standards

- Product tested to 750 lb (340.2 kg) static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18") (113.4 kg from 45.72 cm)
- Tested to 184 lbs (83.5 kg) Puncture Resistance according to ASTM D4833-07
- Meets or exceeds the requirements of ANSI/BIFMA X5.4-205

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

### Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies

Model	RES70
Weight	130 lbs / 59 kg

Dimensions	in	cm
Seat Height	15.6"	39.6
Seat Width	17.7"	45
Overall Height	34.5"	87.6
Overall Depth	64.3"	163.3
Overall Width	26"	66
Arm Height	21"	53.3

### Finishes

See Design Guide for finish options.

### Options

- Bolt-down kit
- Factory Ballasting (50 lbs / 22.7 kg)

*\*Ballastable up to 50 pounds (22.7 kg) of dry sand or gravel. Factory ballasting must be communicated at time of order; products are not field ballastable.*

### Assembly

None required.

*\*Intended for indoor use only*

