

# Titan®

## Multi-Purpose Unit



### Fabrication & Material

Cut, formed, welded steel, powder coated steel.  
All internal structural components shall be constructed from steel of 16-gauge or heavier. For all other components, 20-gauge or thicker steel shall be used, unless stated otherwise.  
**Optional High pressure laminate:** 45 lb (20.4 kg) density M3 grade particle board with durable high-pressure laminate surface and 2mm PVC edge (Wild Cherry Standard).  
Made in the U.S.A.

### Warranty

Multi-Purpose Unit has a 10-year limited replacement warranty. Optional power supply and LED light have a 1-year replacement warranty.

### Maintenance

Norix recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of powder coated steel.  
**Decorative Laminate:** Norix recommends the use of Simple Green® or an equivalent cleaning product.

### Installation

Secure to wall at user discretion through hole locations in back of unit. Wall-mounting hardware not supplied by Norix.

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

**Model** TNT4039  
**Weight** 315 lbs / 143 kg

Dimensions	in	cm
Width	30"	76.2
Depth	24"	61
Height	78"	198.1

### Finishes

See Design Guide for finish options.

### Options

- **TNT4139:** Laminate Door
- Coat Hook & Mirror
- LED Light & Power Supply Kit
- Power Supply

### Assembly

None required.

*\*Intended for indoor use only*

