

# Vesta™ Junior

## Armless Chair



Model	VA670
Weight	19 lbs / 8.6 kg

### Fabrication & Material

One-piece, rotationally-molded polyethylene with lightly textured maintenance-free surface which allows for easy cleaning. Ligature resistant design with no internal openings. Tamper-resistant steel-encased nylon glides for floor protection. Molded-in access port with a threaded screw cap for ballast weighting capability. High-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution, and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability. Made in the U.S.A.

### Warranty

10 year limited replacement warranty.

### Maintenance

**Seats** - For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexide® or Oxivir Five 16®) per manufacturers' instructions.

**Optional Upholstery** - Refer to Upholstery Manufacturer's cleaning instructions.

### Performance Test Standards

- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18") (113.4 kg from 45.7 cm)
- Tested to 750 lb (340.2 kg) static load

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

### Flammability Test Standards - Upholstered Chair

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies

### Flammability Test Standards - Non-Upholstered Chair

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items

Dimensions	in	cm
Seat Height	16"	40.6
Seat Width	19"	48.3
Overall Height	30"	76.2"
Overall Depth	16.5"	41.9
Width	19"	48.3"
Upholstery	yd	m
COM	1	0.9

*\*View our upholstery selection on our website. Fabric Grades B - H and COM available.*

### Finishes

See Design Guide for finish options.

### Options

- Upholstered Seat
- TB133 Upholstery Upgrade
- Bolt-Down Kit
- Ganging Kit
- Factory Ballasting (50 lbs / 22.7 kg)

*\*Ballastable up to 100 pounds (45.4 kg) of dry sand or gravel. On site ballast materials not supplied by Norix.*

### Assembly

None required

*\*Intended for indoor use only*

