



Fabrication & Material

One-piece, rotationally-molded, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). The commercial-grade polyethylene material is also FDA-approved. Premium TruColor™ polymer is fully compounded for superior color consistency and durability. Made in USA.

Warranty

10 year limited replacement warranty

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers’ instructions.

Performance Test Standards

- Product tested to 500 lbs / 226.8 kg static load.

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- 16CFR 1500-14 Flammability
- 16CFR 1303 Lead Content in Surface Coating
- CPSIN Sec 01 Lead Content in Substrate
- CPSIA Sec 08 Phlate Content
- Meets or exceeds the requirements of ANSI/BIFMA X5.4-2012
- Meets or exceeds ASTM F963

Model	AM10
Weight	22 lbs / 10 kg

Dimensions	in	cm
Seat Height	14.3"	36.3
Width	17.5"	39.9
Length	43"	109.2
Overall Hight	22"	55.9

Finishes

See Design Guide for finish options.

Options

- On site Ballasting (50 lbs / 22.7 kg)  
*\*Ballastable up to 50 lbs (22.7 kg) of dry sand or gravel. On site ballast materials not supplied by Norix.*

Assembly

None required.

Patents

Patents pending.

*\*Intended for indoor use only*

