

Boulder™

End Arm Beam Seating



Dimensions	in	cm
Seat Height	18"	45.7
Seat Width	17"	43.2
Seat Depth	16"	40.6
Overall Depth	25"	63.5
Arm Height	24"	61

Finishes

See Design Guide for finish options.

Options

- Glides
- Bolt-Down

Assembly

None required.

**Intended for indoor use only*

Model	Weight		Width		Height	
	lbs	kg	in	cm	in	cm
C213-2 (2 seat)	87	221	44"	111.8	31.4"	79.8
C213-3 (3 seat)	118	299.7	65"	165.1		
C213-4 (4 seat)	153	388.6	86"	218.4		

Fabrication & Material

Base Frame: Tubular steel, bent and welded to provide arm or armless in-line seating. Standard configurations for 2 to 4 people. Flat steel plate welded to the frame at each seat location to provide strength, support, and a mounting platform on which the seat is attached. 2" (5.1 cm) diameter, 14 gauge steel with 11 gauge steel seat supports.

Seats: One-piece seat and back. Smooth maintenance free surface allows for easy cleaning. Molded-in threaded steel inserts provide for tamper resistant attachment to base frame. Rotationally molded, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability.

Warranty

10 year limited replacement warranty.

Maintenance

Frame: Norix recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of powder coated steel.

Seats: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

Installation

For bolt-down application, fasten to floor. Floor mounting hardware included.

Performance Test Standards

- Product tested to 1,000 lb (453.6 kg) static load
- Product dynamic drop tested to a relative impact force of two times ANSI/BIF-MAX 5.4 15.4.2012 (250 lbs. from 18")(113.4 kg from 45.7 cm).

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture

