

# Elle

## 3-Seat Table



<b>Model</b>	EL52
<b>Weight</b>	39 lbs / 17.7 kg

<b>Dimensions</b>	<b>in</b>	<b>cm</b>
Height	22.4"	56.9
Width	55.2"	140.2
Depth	26"	66

### Finishes

See Design Guide for finish options.

### Options

- Ganging Kit
- Bolt-Down Kit
- On site Ballasting (50 lbs / 22.7 kg)

*\*Ballastable up to 50 lbs (22.7 kg) of dry sand or gravel. On site ballast materials not supplied by Norix.*

### Assembly

None required.

### Patents

Patents pending.

*\*Intended for indoor use only*

### Fabrication & Material

One-piece, rotationally-molded, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). The commercial-grade polyethylene material is also FDA-approved. Premium TruColor™ polymer is fully compounded for superior color consistency and durability. Made in USA.

### Warranty

10 year limited replacement warranty.

### Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

### Performance Test Standards

- Product tested to 500 lbs (226.8 kg) static load.

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

### Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- 16CFR 1500-14 Flammability
- 16CFR 1303 Lead Content in Surface Coating
- CPSIN Sec 01 Lead Content in Substrate
- CPSIA Sec 08 Phlate Content
- Meets or exceeds ASTM F963

