



Fabrication & Material

Constructed of wood, 2.5" (6.4 cm) thick foam, enclosed wood panel with secure hardware and finished with upholstery. Optional plinth or steel base. Made in the U.S.A.

Warranty

10 year limited replacement warranty.

Maintenance

Refer to upholstery manufacturer's cleaning instructions for specific fabric.

Installation

Required for Ganging plates and Bolt-down.

Performance Test Standards

- Product tested to 750 lb (340.2 kg) static load
- Meets the requirements of ANSI/BIFMA X5.4-2012

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies

Model	FN
Weight	49 lbs / 22.2 kg (Plinth Base)
	57 lbs / 25.9 kg (Steel Base)

Dimensions	in	cm
Height	18.5"	47
Width	30"	76.2
Upholstery	yd	m
COM Total	2.8	2.6
COM Seat	2.8	2.6

*View our upholstery selection on our website.
Fabric Grades B - H and COM available.

Finishes

See Design Guide for finish options.

Options

- TB133 Upholstery Upgrade
- Power (Max of 2)
- Ganging Kit
- Bolt-down
- Factory Ballasting (50 lbs / 22.7 kg)
(Plinth Base only)

**Ballastable up to 50 lbs (22.7 kg) of dry sand or gravel. On site ballast materials not supplied by Norix.

*Intended for indoor use only

