

DuraVision™ Mirror

Full Dome



Fabrication & Material

Mirror: 1/8" (0.3 cm) polycarbonate with a pure silver reflective coating on inside surface and a tensile strength of 9,400 psi. Fully enclosed foam insert fills cavity to reduce flexing and enhance strength. 360° view.

Frame: 3/16 x 1" (0.5 x 2.5 cm) steel has recessed holes for fastening to any solid flat surface. Powder coated to provide durable smooth finish.

Warranty

3 year limited replacement warranty.

Maintenance

When cleaning stainless steel, Norix recommends the use of a cleaner made especially for stainless steel products.

Installation

Installation required. Refer to manufacturer instructions; confirm surface material for specification of correct fittings (mounting hardware not included).

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Model	MFD-18
Weight	6.2 lbs / 2.8 kg

Dimensions	in	cm
Mirror Diameter	18"	45.7
Frame Diameter	20"	50.8
Depth	6.75"	17.1

Finishes

- **Mirror:** Silver
- **Frame:** Almond

Options

- 24" (61 cm) Diameter

Assembly

Fit mirror and foam backing to frame.
Attach to ceiling or wall.

**Intended for indoor use only*

