

# DuraVision™ Wall Mirror

## Rectangle



### Fabrication & Material

**Mirror:** 0.04" (1 mm) stainless steel with bright annealed or #8 mirror finish on one side with a tensile strength of 103,121 psi.  
**Frame:** ¼ x 1" (0.6 x 2.5 cm) steel has recessed holes for fastening to any solid flat surface. Powder coated to provide durable smooth finish.

### Warranty

3 year limited replacement warranty.

### Maintenance

When cleaning stainless steel, Norix recommends the use of a cleaner made especially for stainless steel products.

### Installation

Installation required. Refer to manufacturer instructions; confirm surface material for specification of correct fittings (mounting hardware not included).

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

**Model** MFSST-REC-1620

**Weight** 6.8 lbs / 3.1 kg

Dimensions	in	cm
Mirror	14" x 18"	35.6 x 45.7
Frame	16" x 20"	40.6 x 50.8
Depth	0.25"	0.6

### Finishes

- Mirror:** Bright Mirror Finish
- Frame:** Almond

### Assembly

Align mirror holes with frame holes.  
Attach to wall or embed plate.

*\*Intended for indoor use only*

