

# DuraVision™ Wall Mirror

## Round



### Fabrication & Material

**Mirror:** 0.04" (1 mm) stainless steel with bright annealed or #8 mirror finish on one side with a tensile strength of 103,121 psi.

**Frame:** ¼ x 1" (0.6 x 2.5 cm) steel has recessed holes for fastening to any solid flat surface. Powder coated to provide durable smooth finish.

### Warranty

3 year limited replacement warranty.

### Maintenance

When cleaning stainless steel, Norix recommends the use of a cleaner made especially for stainless steel products.

### Installation

Installation required. Refer to manufacturer instructions; confirm surface material for specification of correct fittings (mounting hardware not included).

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

**Model** MFSST-RND-1600

**Weight** 4.6 lbs / 2.1 kg

Dimensions	in	cm
Mirror Diameter	14"	35.6
Frame Diameter	16"	40.6
Depth	0.25"	0.6

### Finishes

- **Mirror:** Bright Mirror Finish
- **Frame:** Almond

### Assembly

Align mirror holes with frame holes.  
Attach to wall or embed plate.

*\*Intended for indoor use only*

