

DuraVision™ Mirror

Quarter Dome



Fabrication & Material

Mirror: 1/8" (0.3 cm) polycarbonate with a pure silver reflective coating on inside surface and a tensile strength of 9,400 psi. Fully enclosed foam insert fills cavity to reduce flexing and enhance strength. 90° view.

Frame: 3/16" x 1" (0.5 x 2.5 cm) steel has recessed holes for fastening and slotted flange for mirror. Powder coated to provide durable smooth finish.

Warranty

3 year limited replacement warranty.

Maintenance

When cleaning stainless steel, Norix recommends the use of a cleaner made especially for stainless steel products.

Installation

Installation required. Refer to manufacturer instructions; confirm surface material for specification of correct fittings (mounting hardware not included).

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Model	MQD-12
Weight	7.2 lbs / 3.3 kg

Dimensions	in	cm
Length	19"	48.3
Height	9.5"	24.1
Depth	13.5"	34.3

Finishes

- **Mirror:** Silver
- **Frame:** Almond

Options

- 18" (45.7 cm) Mirror

Assembly

Fit mirror and foam backing to frame.
Attach to ceiling or wall.

**Intended for indoor use only*

